

[EXECUTIVE ORDER NO. 769, November 19, 2008]

DECLARING AND DELINEATING THE CAGAYAN DE ORO PORT ZONE UNDER THE ADMINISTRATIVE JURISDICTION OF THE PHILIPPINE PORTS AUTHORITY

WHEREAS, the Port of Cagayan de Oro is one of the major and busiest ports in the country;

WHEREAS, there is a need to expand the Port of Cagayan de Oro for planning purposes to accommodate projected increases in port traffic and to program the development of the necessary port facilities to support the demands of the shipping trade within the region;

NOW, THEREFORE, I, GLORIA MACAPAGAL-ARROYO, President of the Philippines by virtue of the power vested in me by law, do hereby order:

SECTION 1. The territorial jurisdiction of the Port of Cagayan de Oro is hereby realign/relocate the boundary and particularly described as follows:

"Beginning at point marked 1 on the plan,

thence to point 2	at a distance of 20.83m	with bearing S6128'E
thence to point 3	at a distance of 2.92m	with bearing N6205'E
thence to point 4	at a distance of 7.52m	with bearing S5226'E
thence to point 5	at a distance of 113.81	with bearing N3500'E
thence to point 6	at a distance of 272.89m	with bearing N4453'W
thence to point 7	at a distance of 26.40m	with bearing N1939'E
thence to point 8	at a distance of 1,513.13m	with bearing N9000'E
thence to point 9	at a distance of 2,334.74m	with bearing S0000'E
thence to point 10	at a distance of 1,000.00m	with bearing N9000'W
thence to point 11	at a distance of 100.00m	with bearing N7344'W
thence to point 12	at a distance of 120.30m	with bearing N6320'W
thence to	at a distance of	with bearing

point 13	226.61m	N3301'W
thence to point 14	at a distance of 321.69m	with bearing N2552'W
thence to point 15	at a distance of 69.23m	with bearing N0651'W
thence to point 16	at a distance of 182.40m	with bearing N5225'W
thence to point 17	at a distance of 72.56m	with bearing N4943'W
thence to point 18	at a distance of 55.78m	with bearing N2002'E
thence to point 19	at a distance of 30.02m	with bearing N0510'W
thence to point 20	at a distance of 17.39m	with bearing N0034'E,
thence to point 21	at a distance of 56.38m	with bearing N1448'W
thence to point 22	at a distance of 29.81m	with bearing N2516'W
thence to point 23	at a distance of 29.67m	with bearing N6506'W
thence to point 24	at a distance of 30.07m	with bearing S8611'W
thence to point 25	at a distance of 30.48m	with bearing S4859'W
thence to point 26	at a distance of 24.08m	with bearing S4138'W
thence to point 27	at a distance of 40.98m	with bearing S8423'W
thence to point 28	at a distance of 7.32m	with bearing N1631'E,
thence to point 29	at a distance of 235.51m	with bearing N1632'E
thence to point 30	at a distance of 58.24m	with bearing N0013'W
thence to point 31	at a distance of 3.24m	with bearing N2010'W
thence to point 32	at a distance of 30.98m	with bearing N0024'W
thence to point 33	at a distance of 24.03m	with bearing N0022'W
thence to point 34	at a distance of 27.24m	with bearing N0034'W
thence to point 35	at a distance of 45.95m	with bearing N1739'W
thence to point 36	at a distance of 97.49m	with bearing N1739'W
thence to point 37	at a distance of 2.71m	with bearing N7145'W
thence to point 38	at a distance of 30.17m	with bearing N2050'W
thence to	at a distance of	with bearing