STATUTORY RULES OF NORTHERN IRELAND

2015 No. 406

CLEAN AIR

The Smoke Control Areas (Exempted Fireplaces) (Amendment No.2) Regulations (Northern Ireland) 2015

Made - - - -	*9th December 2015*
Coming into operation	*31st January 2016*

The Department of the Environment makes the following Regulations in exercise of the powers conferred by Article 17(7) of the Clean Air (Northern Ireland) Order 1981(**1**).

The Department is satisfied that the classes of fireplace set out in column 1 of the Schedule can, subject to the conditions set out in column 2 of the Schedule, be used for burning fuel other than authorised fuels(**2**) without producing any smoke or a substantial quantity of smoke.

Citation commencement and interpretation

1.—(1) These Regulations may be cited as the Smoke Control Areas (Exempted Fireplaces) (Amendment No.2) Regulations (Northern Ireland) 2015 and come into operation on 31st January 2016.

(2) In these Regulations, "the Principal Regulations" mean the Smoke Control Areas (Exempted Fireplaces) (No.2) Regulations (Northern Ireland) 2013(**3**).

Amendments to the Principal Regulations

2.—(1) The Schedule to the Principal Regulations is amended in accordance with paragraphs (2) to (5).

(2) The classes of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the words—

(a) "Rais Juno";

(b) "RAIS VIVA 98";

(c) "Sherborne SE NS-3C, Chesham SE NS-3B, Burford SE NS-3A"; and

(d) "Vista Magnifico SE NS-1 and Vista Perfetto SE NS-2";

(**1**) S.I. 1981/158 (N.I. 4), to which there are amendments not relevant to these Regulations.
(**2**) Fuels declared by the Department of the Environment to be authorised fuels for the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981 are specified in S.R. 2013 No. 205, as amended by S.R. 2014 No. 249.
(**3**) S.R. 2013 No. 292, as amended by S.R. 2014 No. 166, S.R. 2014 No. 294 and S.R. 2015 No. 274.

and the respective conditions set out in the second column under the heading "(2) Conditions" are omitted.

(3) In the class of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the word—

"Senza",

for the words "Senza UK w/o sideglass and Senza UK w/ sideglass", substitute the words "Senza UK with sideglass and Senza UK without sideglass".

(4) In the classes of fireplace described in the first column under the heading "(1) Class of fireplace" beginning with the words—

(a) "Newbourne 40 and Newbourne 50 Freestanding stoves";

(b) "Newbourne 40 inset stove";

(c) "Pevex 60 convector stove";

(d) "Pevex Bohemia X 30, X 40, X 40 Cube, X 50 and X 60 multi-fuel stoves";

(e) "Pevex Bohemia X 40 Inset multi-fuel appliance";

(f) "Pevex Serenity 40D inset multi-fuel appliance";

(g) "Serenity 40 FS, Serenity 40 LS, Serenity 40 FW stoves";

(h) "Serenity 50FS, Serenity 50LS, Serenity 50FW and Serenity 50 Ped stoves"; and

(i) "Serenity 50 Inset stove",

for each time that they appear, for the address of the manufacturer ("Pevex Enterprises Ltd"), substitute "Unit MP7, Kirrawah Business Park, Newbourne Road, Nr Woodbridge, IP12 4PR".

(5) At the appropriate places in the Schedule, insert the classes of fireplace and the respective conditions set out in the Schedule to these Regulations.

Sealed with the Official Seal of the Department of the Environment on 9th December 2015.

L.S.

Dave Foster
A senior officer of the
Department of the Environment

SCHEDULE Regulation 2

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
Aarrow ECB5 Plus SC 5kW and ECB7 Plus SC 7kW wood-burning stoves manufactured by Arada Limited, The Fireworks, Weycroft Avenue, Axminster, Devon, EX13 5HU.	Operation & Installation manual dated July 2015 reference "ECB Plus SC Rev 06".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Aduro 16 5kW wood-burning stove manufactured by Aduro AS, Beringvej 17, DK-8361, Hasselager, Denmark.	Instruction manual dated July 2015 and reference "Version 1 – 2015.07". The appliance must be fitted with a permanent stop to prevent closure of the secondary air slider beyond the 67% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Andalo 2, Lovero 2, Solaro 2 6.7 kW multifuel stoves manufactured by Drooff Kaminöfen GmbH & Co. KG, Keffelker Str. 40, D-59929 Brilon, Germany.	Instructions manual reference "Instructions: Installation, Operation, Function, Maintenance" and technical information dated July 2015 reference "Andalo 2-Lovero 2-Solaro 2, technical data" version SDK/0715. The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
Andorra model F9489, Sevilla model F9489 V, Delia model F9489 A, Cadiz model F9489 C, Rodano model F9489 P, Atika model F9489 D, Zion Keramik model F9489 K, Zion Serpentino model F9489 F, Andorra Exclusive model F9489 O and Toledo model F9489 I 5kW multifuel stoves manufactured by THORMA Vyroba k.s., Šavol'ská cesta 323/1, 986 01, Fil'akovo-Priemyselný obvod, Slovakia.	Installation and Operation Manual dated 27th July 2015 reference "ANDORRA – Version A". The appliance must be fitted with a modified air regulator which has a permanent opening of 620mm^2 when in the fully closed position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Aquila 450 Contemporary, Corvus 450 Traditional, Corvus 450 Contemporary and Vega 450 Traditional 4.5kW multifuel inset stoves manufactured	Instruction manual dated 28th July 2015, reference: "Aquila 450 / Corvus 450 / Vega 450 Solid Fuel Stoves Manual Version 1.1 Issued 28/07/2015 Inset Versions Supplement".	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
by F.E. Robinson (Hooton) Limited, Station Works, Hooton Road, Hooton, South Wirral, CH66 7NF.		a result of treatment with wood-preservatives or coatings.
Arte 1Vh 66 – A – P3, Arte 1Vh 66 – A1 – P3, Arte 1Vh 66 X – A – P3 and Arte 1Vh 66 X – A1 – P3 6.6kW wood burning inset roomheaters manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany.	Instruction manual dated September 2014 reference "Version 09 / 2014". The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 8mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Arte 2LRh 66 – A – P3 and Arte 2LRh 66 – A1 – P3 12kW wood burning inset roomheaters manufactured by Spartherm Feuerungstechnik GmbH, Maschweg 38, 49324 Melle, Germany.	Instruction manual dated July 2015 reference "Version 07 / 2015". The appliance must be fitted with a mechanical stop to prevent closure of the air control beyond the 14mm open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Ashdale FB2MF 7kW multifuel stove manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Technical manual dated 13th May 2015 reference "Document FB2MF 0101 Version 3". The appliance must be fitted with a mechanical stop to prevent closure of the secondary air slider beyond the 12mm open position and the tertiary air control will be fixed in the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result