STATUTORY RULES OF NORTHERN IRELAND

2013 No. 292

CLEAN AIR

The Smoke Control Areas (Exempted Fireplaces) (No. 2) Regulations (Northern Ireland) 2013

Made - - - - 10th December 2013

Coming into operation 13th January 2014

The Department of the Environment makes the following Regulations in exercise of the powers conferred by Article 17(7) of the Clean Air (Northern Ireland) Order 1981(**1**).

The Department is satisfied that the classes of fireplaces prescribed in column (1) of the Schedule can, subject to the conditions prescribed in column (2) of the Schedule, be used for burning fuel other than authorised fuels(**2**) without producing any smoke or a substantial quantity of smoke.

Citation and commencement

1. These Regulations may be cited as the Smoke Control Areas (Exempted Fireplaces) (No. 2) Regulations (Northern Ireland) 2013 and shall come into operation on 13th January 2014.

Exempted Fireplaces

2. The classes of fireplaces prescribed in column (1) of the Schedule shall, subject to the conditions prescribed in column (2) of the Schedule, be exempt from the provisions of Article 17 of the Clean Air (Northern Ireland) Order 1981.

Revocation

3. The Smoke Control Areas (Exempted Fireplaces) Regulations (Northern Ireland) 2013(**3**) are revoked.

(**1**) S.I. 1981/158 (N.I. 4)

(**2**) Fuels declared by the Department of the Environment to be authorised fuels for the purposes of Article 2(2) of the Clean Air (Northern Ireland) Order 1981 are specified in S.R. 2013 No. 205.

(**3**) S.R. 2013 No. 198

Sealed with the official seal of the Department of the Environment on 10th December 2013.





Wesley Shannon
A senior officer of the
Department of the Environment

SCHEDULE Regulation 2

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
Any fireplace specially designed or adapted for combustion of liquid fuel.		
Any fireplace (other than a fireplace fired by pulverised fuel) constructed on or after 1st July 1965 and installed before 1st September 1970 and equipped with mechanical stokers, or adapted between those dates for use with such stokers.		No fuel shall be used other than that for which the mechanical stoker was designed.
Any fireplace designed to burn coal (other than a fireplace fired by pulverised coal) with a heating capacity exceeding 160 megajoules per hour constructed and installed on or after 1st July 1965 and equipped with mechanical stokers or adapted on or after that date for use with such stokers.		No fuel shall be used other than that for which the mechanical stoker was designed.
18i and 60i stoves manufactured by Jetmaster Fires Limited, Unit 2 Peacock Trading Estate, Goodwood Road, Eastleigh, Hampshire, SO50 4NT.	Installation and use instruction manual reference: "Part No 106870 Issue No. 1" dated February 2010 and supplementary instruction manual reference: "Part No 106872 Issue No. 1" dated May 2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
100SE Smoke Exempt Woodburning Stove manufactured by ESSE Engineering Limited, Long Ing, Barnoldswick, Lancashire. BB18 6BN.	The manufacturer's instruction manual reference 100SE Issue 1. A permanent stop must be in place on the secondary air inlet to prevent closure beyond the 50% open position.	Untreated dry wood with a maximum moisture content of 20%, maximum length of 200mm and maximum width or diameter of 120mm. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Aarrow Signature 5 SC, Aarrow Ecoburn 5 SC,	Instruction manual references "Rev 02" dated April 2010.	Wood logs. The fuel must not contain halogenated organic

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
Hamlet Solution 5 SC and Villager Espirit 5 SC Stoves manufactured by Arada Limited, The Fire Works, Millwey Industrial Estate, Axminster, Devon. EX13 5HU.	All the appliances will be fitted with a mechanical stop to prevent closure of the air control beyond 20mm from the closed position and 50mm beyond the fully open position.	compounds or heavy metals as a result of treatment with wood preservatives or coatings.
Acquisitions Bloomsbury 5kW stove manufactured by Esse Engineering Limited, Ouzledale Foundry, Long Ing, Barnoldswick, BB18 6BN.	Instruction manual references "01/12(PP)" dated January 2012. The fitting of a system to prevent closure of the air controls beyond the 50% open position must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Acquisitions Cannonbury 4 and 5 manufactured by Esse Engineering Ltd, The Ouzledale Foundry, Long Ing, Barnoldswick, Colne, Lancashire, BB8 6BN.	Installation and Operating Instruction manual reference "v71 of 09/11/2010" dated 09/11/2010.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
ACR Astwood Multifuel stove AW1MF manufactured by ACR Heat Products Ltd, Unit 1 Weston Works, Weston Lane, Tyseley, Birmingham, B11 3RP.	Instruction manual references "AW1MF 0101 Version 3" dated 28/01/2013. A mechanical stop to prevent closure of the secondary air control lever beyond 12mm open must be implemented.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Aduro 3D, 8D, 10D, 11D and Asgård 1D, 2D and 7D wood burning stoves manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	Instruction manual references "Pevex1001/AH/ver1" and dated June 2011. Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Aduro 9D wood burning stove manufactured by Aduro A/S, Silkeborgvej 765 8220, Brabrand, Denmark.	Instruction manual references "Pevex1002/AH/ver1" and dated June 2011. Fitted with permanent stops to ensure that the primary and secondary air controls do not close beyond 95% and 50% respectively.	Dry wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.

(1) Class of fireplace	*(2) Conditions*	
	The fireplace must be installed, maintained and operated in accordance with the following specifications:	*Permitted fuels (other than authorised fuels):*
Alberg 7 manufactured by Elite Group Trading Limited, Room 1208 Kak Tak Commercial Building 317-319 Des Voeux Road, Central Hong Kong 999077.	Instruction manual references "EGTL03A Version 1.4" dated 21st December 2011.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Alpha I model number AL905-SE Wood Burning Stove. Manufactured by Hi-Flame Fireplace UK Limited Unit 5A Holmes Chapel Business Park Manor Lane Holmes Chapel Cheshire CW4 8AF.	Instruction manual references "HF277-SE/UK-NI-ROI/ V2D.18-07-12" dated July 2012. Fitted with a mechanical stop to prevent closure of the main air control beyond the 50% open position.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Alpha II model number AL907-SE Wood Burning Stove. Manufactured by Hi-Flame Fireplace UK Limited Unit 5A Holmes Chapel Business Park Manor Lane Holmes Chapel Cheshire CW4 8AF.	Instruction manual references "AL907-SE/UK-NI-ROI/V3-D.14-07-12" dated July 2012. Fitted with a mechanical stop to prevent secondary air control closure beyond the 20% open position, and a 70mm opening of the door rope seal to allow a constant flow of air when sold into smoke control areas.	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.
Amalia 5 and Oppdal 5 multifuel stoves manufactured by Broseley Fires Knights Way Battlefield Ent Park	Instruction manual references "GB12A Version 1" dated February 2013. The appliance must be fitted with a permanent stop, preventing closure of the	Wood logs. The fuel must not contain halogenated organic compounds or heavy metals as a result of treatment with wood-preservatives or coatings.