Class or description of hoist or hoistway.	Requirements which shall not apply.	Conditions or limitations (if any).
10. Drop-pit hoists used for raising or lowering wheels detached from railway rolling-stock.	Sub-sections (3) to (7).	—
11. Hoists in the case of which the doors of the hoistway are of solid construction and the interior surfaces of the said doors and of the hoistway opposite to any side of the cage in which there is an opening are, throughout the height of travel of the cage, smooth and flush with each other and not more than half-an-inch, measured horizontally, from the edge of the floor of the cage.	Sub-section (7) (*b*).	—

Postponement of Certain Requirements.

ORDER, DATED 10TH DAY OF MAY, 1939, MADE BY THE MINISTRY OF LABOUR UNDER SECTION 162 OF THE FACTORIES ACT (NORTHERN IRELAND), 1938.

1939. No. 74.

The Ministry of Labour for Northern Ireland, in pursuance of the powers conferred on it by sub-section (2) of Section 162 of the Factories Act (Northern Ireland), 1938, and of all other powers enabling it in that behalf, hereby makes the following Order :—

1.—The date of coming into operation of the requirements contained in sub-section (2) of Section 14 of the Act shall be postponed until the 1st January, 1941, as respects factories in which the main transmission machinery is driven wholly or partly by water-power.

2.—The date of coming into operation of the requirements contained in sub-sections (3), (4), (5) and (7) of Section 23 of the Act shall be postponed until the 1st January, 1941, as respects hoists or lifts constructed or reconstructed before the passing of the Act in warehouses to which the provisions of Section 23 are applied by sub-section (3) of Section 109 of the Act, subject to the condition that the hoist or lift shall be securely fenced so far as is reasonably practicable.